| Seat No.: | Enrolment No. |
|-----------|---------------|
| | |

GUJARAT TECHNOLOGICAL UNIVERSITY

BE - SEMESTER-III(New) • EXAMINATION - WINTER 2016

Subject Code:2130003 Date:31/12/2016

Subject Name:Mechanics of Solids

Time:10:30 AM to 01:00 PM Total Marks: 70

Instructions:

- 1. Attempt all questions.
- 2. Make suitable assumptions wherever necessary.
- 3. Figures to the right indicate full marks.

| | | | MARKS |
|-----|------------|--|------------|
| Q.1 | | Short Questions: | 14 |
| | 1 | Two unlike parallel forces, will form a (Couple, Bending Moment, Shear force). | |
| | 2 | A particle is said to be in when the resultant force acting on it is zero. (Equilibrium, Stable, Unstable) | |
| | 3 | The process of finding components of a force is calledof forces. (Resolution, Splitting, Composition) | |
| | 4 | Define Law Of Transmissibility. | |
| | 5 | The Relation between Shear force and Bending moment is | |
| | 6 | A cylinder is a surface of revolution generated by revolving aline about a fixed axis. (Straight, circular) | |
| | 7 | Co-efficient of static friction will always bethan the coefficient of kinetic friction. (greater, equal, lesser) | |
| | 8 | The maximum value of Poisson's ratio for most of the engineering material is (0.5, 1,1.5) | |
| | 9 | Young's modulus of elasticity for a perfectly rigid body is(zero, infinity) | |
| | 10 | The point where the Shear force is maximum, slope of the bending moment is (maximum, minimum, zero) | |
| | 11 | In a beam of I-section, the maximum shear stress is carried by the(web, flange) | |
| | 12 | A t the point of contraflexurechanges it's sign. (shear force, bending moment, axial force) | |
| | 13 | Shear stresses on principal planes are(zero, maximum, minimum) | |
| | 14 | For an element in pure shear, principal planes are oriented at to the axis. $(45^0, 90^0)$ | |
| Q.2 | (a) | State and explain Varignon's theorem. | 03 |
| | (b) | | 04 |
| | (c) | | 07 |
| | (c) | At a point in a strained material the state of stress is as shown in | 07 |
| | (0) | figure 2. Determine (i) Location of Principal planes (ii) Principal | J , |

stresses. (iii) Maximum shear stress and location of plane on which it acts.

| Q.3 | (a) | For pure bending, prove that the neutral axis coincides with the centroid of the cross section. | 03 |
|------------|------------|---|-----|
| | (b) | | 04 |
| | (c) | A solid steel shaft is subjected to a torque of 45 kN m. If the angle of twist is 0.5° per meter length of shaft and shear stress is not to exceed 90 N/mm². Find: (i) Suitable diameter of shaft (ii) Final maximum shear stress and angle of twist for diameter of shaft selected. Take G= 80 GPa. | 07 |
| 0.0 | () | OR . | 0.2 |
| Q.3 | (a) | State assumptions made in theory of pure bending. | 03 |
| | (b) | For a hollow circular section whose external diameter is twice the internal diameter, find the ratio of maximum shear stress to average shear stress. | 04 |
| | (c) | What should be the value of Θ in figure 3 which will make the motion of 1000N block down the plane to impend? The coefficient | 07 |
| | | of friction for all contact surfaces is 1/3. | |
| Q.4 | (a) | rigidity. | 03 |
| | (b) | In a tension test, a bar of 20 mm diameter undergoes elongation of 14 mm in a gauge length of 150 mm and a decrease in diameter of 0.85 mm at a tensile load of 6 kN. Determine the two physical constants Poisson's ratio and modulus of elasticity of the material. | 04 |
| | (c) | Determine the centroid of the plane area in which a circular part of | 07 |
| | | 40 mm radius, has been removed as shown in Figure 4. | |
| | | OR | |
| Q.4 | (a) | Determine the surfaces area and volume of a right circular cone with radius of base R and height h using Pappus-Guldinus theorem. | 03 |
| | (b) | Derive expression of moment of inertia of triangle by first principal. | 04 |
| | (c) | A 6 m long steel rod having 20 mm diameter is connected to two grips and each end at a temperature of 120^{0} C. Find (i) pull exerted when temperature falls to 40^{0} C and ends do not yield, (ii) pull exerted when temperature falls to 40^{0} C and ends yield by 1.1 mm, (iii) the shortening allowed for no stress at 40^{0} C and (iv) the minimum final temperature for shortening of 1.1 mm. Take $E_{\text{steel}} = 205$ GPa, $\alpha_{\text{steel}} = 11$ X $10^{-6}/{}^{0}$ C. | 07 |
| Q.5 | (a) | | 03 |
| | (b) | A solid circular steel shaft of diameter 75 mm can resist maximum shear stress of 75 N/mm ² . If shaft is rotating at 150 rpm, calculate the power transmitted by shaft. Also calculate the angle of twist for 1.4m long shaft if G=100 GPa. | 04 |
| | (c) | Draw Shear Force and Bending Moment diagram for the beam as shown in figure 5. | 07 |
| | | OR | _ |
| Q.5 | (a) | *1 | 03 |
| | (b) | A steel bar of rectangular cross section is 60 mm wide and 50 mm thickness is subjected to an axial pull of 85 kN. Calculate Normal. | 04 |

Tangential and Resultant stresses on an inclined plane at 30^0 to the cross section of bar.

(c) A weight 750 N just starts moving down a rough inclined plane supported by a force of 250 N acting parallel to the plane and it is at the point of moving up the plane when pulled by a force of 350N parallel to the plane. Find the inclination of the plane and the coefficient of friction between the inclined plane and the weight.

07


