

Seat No.: _____

Enrolment No. _____

GUJARAT TECHNOLOGICAL UNIVERSITY

BE - SEMESTER-V (NEW) - EXAMINATION – SUMMER 2018

Subject Code:2151909

Date:04/05/2018

Subject Name:Heat Transfer

Time:02:30 PM to 05:00 PM

Total Marks: 70

Instructions:

1. Attempt all questions.
2. Make suitable assumptions wherever necessary.
3. Figures to the right indicate full marks.

	MARKS
Q.1 (a) Define following: (1) Thermal Conductivity (2) Prandtl Number (3) Solid angle	03
(b) State significance of critical radius of insulation and derive its equation.	04
(c) Differentiate (1) Convection and Radiation modes of heat transfer. (2) Natural and Force convection heat transfers.	07
Q.2 (a) Discuss lumped parameter analysis and state its assumptions.	03
(b) A furnace wall is made up of two layers of thickness 250 mm, 100 mm with thermal conductivity of 1.65 and 9.2 W/m °C respectively .The inside is exposed to gases at 1250°C with a convection coefficient of 25 W/m ² °C and the inside surface is at 1100 °C, the outside surface is exposed to air at 25 °C with convection coefficient of 12 W/m ² °C.The overall heat transfer coefficient.	04
(c) Derive equations of temperature distribution and heat transfer for composite cylinder separating two fluids considering heat flow in radial direction.	07
OR	
(c) Write general differential equation of heat transfer for constant area fin. From this obtain temperature distribution and heat transfer equations for fin insulated at the tip.	07
Q.3 (a) Show physical significance of Following non-dimensional numbers: Nu (Nusselt Number), Gr (Grashof Number)	03
(b) Explain concept of thermal boundary layer.	04
(c) Calculate the rate of heat loss from human body which may be considered as a vertical cylinder 300mm in diameter and 175mm high in still air at 15 °C. The skin temperature is 35 °C and emissivity at the skin surface is 0.4. Neglect sweating and effect of clothing. The thermo physical properties of air at mean film temperature are: $K = 0.0263 \text{ w/m } ^\circ\text{C}$ $\nu = 15.53 \times 10^{-6} \text{ m}^2/\text{s}$ $pr = 0.7$ for turbulent flow use $Nu = 0.13(Gr \times Pr)^{0.33}$	07

OR

- Q.3** (a) Explain mean film temperature and bulk mean temperature. **03**
(b) A motor cycle cylinder consists of fins having outside diameter 150 mm and total surface area of 0.27 m². Calculate the rate of heat dissipation from cylinder fins when motorcycle is running at 20 m/s speed. The atmospheric air is at 25 °C and average fin surface temperature is 475 °C. the relevant thermo – physical properties at average temperature of 250 °C are: K = 0.0427 w/m °C
 $\nu = 40.61 \times 10^{-6} \text{ m}^2/\text{s}$ $\text{Pr} = 0.677$
for turbulent flow use $\text{Nu} = 0.036 (\text{Re})^{0.8} (\text{Pr})^{0.33}$
(c) Show by dimensional analysis that for forced convection Nusselt number is the function of Reynolds number and Prandtl number. **07**

- Q.4** (a) Prove that for black body $\lambda_{\text{max}} T = \text{Constant}$. Where λ_{max} = wavelength at which spectral emissive power is maximum and T = absolute temperature of body. **03**
(b) Justify that a good absorber is also a good emitter for radiation heat transfer. **04**
(c) What is radiation shield? Show that presence of n number of radiation shields reduces the radiation heat transfer by a factor of (n+1). **07**

OR

- Q.4** (a) Define : Shape factor, Irradiation, Emissivity **03**
(b) The sun emits maximum radiation at $\lambda = 0.52 \mu\text{m}$. Assuming sun to be a black body, calculate the surface temperature of sun and the total emissive power of the sun's surface at that temperature. **04**
(c) Define Intensity of radiation. Derive relationship between normal intensity and black body total emissive power. **07**
- Q.5** (a) What is condensation? How does drop wise condensation differ from film wise condensation? **03**
(b) Discuss the various regimes in boiling. **04**
(c) Derive an expression for log mean temperature difference of counter flow heat exchanger. **07**

OR

- Q.5** (a) With neat sketch explain classification of heat exchangers based on relative motion of fluids. **03**
(b) What is the fouling factor? Explain their effect in Heat Exchanger design. **04**
(c) A counter flow heat exchanger is employed to cool oil of specific heat $C_p = 2.45 \text{ KJ/Kg}^\circ\text{C}$ with mass flow rate of 0.55 Kg/sec from 115°C to 40 °C by water. The inlet and outlet temperature of cooling water are 15 °C and 75 °C respectively. The overall heat transfer co-efficient is 1450W/m² °C. Using NTU method, calculate: (i) The mass flow rate of water (ii) The effectiveness of heat exchanger (iii) The surface area required. **07**
