Seat No.: _ Enrolment No._

GUJARAT TECHNOLOGICAL UNIVERSITY

BE - SEMESTER-V(New) • EXAMINATION - WINTER 2016

Subject Code:2150608 Date:22/11/2016

Subject Name:Structural Analysis-II

Time: 10:30 AM to 01:00 PM **Total Marks: 70**

Instructions:

- 1. Attempt all questions.
- 2. Make suitable assumptions wherever necessary.
- 3. Figures to the right indicate full marks.

			MARKS
Q.1		Answer the following:	14
	1	Explain stiffness.	
	2	Differentiate between carry over factor and distribution	
	•	factor.	
	3	Define flexibility.	
	4	In a fixed beam of length L if one end sinks by δ , what are the moments and reactions induced at both the ends.	
	5	Explain influence line diagram for a beam.	
	6	Write Castigliano's first theorem.	
	7	Explain rolling loads.	
	8	Differentiate between maximum bending moment at a section	
		and absolute maximum bending moment anywhere in the	
		section due to rolling loads.	
	9	Write Muller-Breslau's principle.	
	10	In a fixed end beam AB of length L, if end B rotates by an	
		angle θ , what are the reactions and moments obtained at both	
		the ends.	
	11	Draw ILD of a moment at fixed end for a cantilever beam AB	
		having length 4m.	
	12	Why stiffness method is more suitable for computer	
	10	programming?	
	13	Write fixed end moments for beam shown in fig1.	
Ω	14	Explain strain energy with illustration. Explain causes of side-sway in plane frame with illustrations.	03
Q.2	(a) (b)	Analyse the beam shown in fig2 by moment distribution	03
	(D)	method. Take EI=constant.	V -7
	(c)	Analyse the beam shown in fig3by slope-deflection method	07
		and draw BMD. Take EI=constant.	
		OR	
	(c)	Analyse the beam shown in fig3 by stiffness method and	07
0.2	(-)	draw BMD.	02
Q.3	(a)	Obtain slope-deflection equations for the beam shown in fig2.	03
	(b)	Calculate the stiffness matrix for the beam shown in fig2.	04
	(c)	For a propped cantilever beam AB, fixed at A and having	07
		roller support at B, of span 5m, draw ILD for R _B . Calculate	
		ordinates of ILD at every 1m interval.	
		OR	
Q.3	(a)	Discuss the criteria to determine the absolute maximum	03
		bending moment and its location for a simply supported beam	
		under rolling concentrated loads.	
	(b)	Draw ILD for R _A and M _A for a beam shown in fig4	04

(c)	Three point loads 50 kN, 70 kN and 90 kN equally spaced 2m respectively, cross a girder of 25 m span from left to right, the 90 kN load leading. Calculate absolute maximum bending moment in the beam and its location.	07		
(a)	State and explain Castigliano's second theorem with example.	03		
(b)	having length 5m and loaded by a UDL of 15 kN/m over	04		
(c)	Fig5 shows simply supported beam AB having varying moment of inertia. It is subjected to an eccentric load.	07		
(a)	021	03		
(a)		UJ		
(b)	Choosing R _B and M _B as redundants, find flexibility matrix for	04		
(c)	Analyse the frame shown in fig8 by Castigliano's second	07		
(a)	Calculate slope-deflection equations for the portal frame as	03		
(b)	E	04		
(c)	Analyse the portal frame as shown in fig9 by flexibility method and draw BMD.	07		
OR				
(a)	Find distribution factors for the frame shown in fig10.	03		
(b)		04		
(c)	Analyse the portal frame as shown in fig10 by flexibility matrix.	07		
	(a) (b) (c) (a) (b) (c) (a)	respectively, cross a girder of 25 m span from left to right, the 90 kN load leading. Calculate absolute maximum bending moment in the beam and its location. (a) State and explain Castigliano's second theorem with example. (b) Calculate deflection at free end B for a cantilever beam AB having length 5m and loaded by a UDL of 15 kN/m over whole span using energy principle. (c) Fig5 shows simply supported beam AB having varying moment of inertia. It is subjected to an eccentric load. Calculate slope at A using energy principle. OR (a) Calculate deflection at free end of a cantilever beam as shown in fig6 using unit load method. Take EI=constant. (b) Choosing R _B and M _B as redundants, find flexibility matrix for beam shown in fig7, Take EI=Constant. (c) Analyse the frame shown in fig8 by Castigliano's second theorem and draw BMD. Take EI=Constant. (a) Calculate slope-deflection equations for the portal frame as shown in fig9. (b) Obtain stiffness matrix for the portal frame as shown in fig9. Canalyse the portal frame as shown in fig9 by flexibility method and draw BMD. OR (a) Find distribution factors for the frame shown in fig10. Carry-out only non-sway analyses for portal frame shown in fig10 by moment distribution method. (c) Analyse the portal frame as shown in fig10 by flexibility		

